



CLEANENERGY®

Waste Oil Heaters That Burn Hot & Save Money

	CE140	CE180	CE250	CE330	CE340
BTU input	140,000	175,000	245,000	325,000	335,000
Fuel Flow Rate	1 GPH	1.2 GPH	1.7 GPH	2.3 GPH	2.4 GPH
Air Flow Output	1700 CFM	1700 CFM	2400 CFM	3700 CFM	
Heat Rise	75°	80°	90°	85°	
Stack Diameter	6"	6"	6"	8"	8"
Electrical	115 VAC/ 20 Amp	115VAC / 20 Amp	115 VAC / 30 Amp	230 VAC / 20 Amp	115 VAC / 20 Amp
Heat Exchanger	14 ga. SS	14 ga. SS	14 ga. SS	14 ga. SS	1/4 carbon steel (ASME SA36)
Flue Tubes	14 ga. SS	14 ga. SS	14 ga. SS	14 ga. SS	2.875" OD, 13/64" wall (Sch 40)
Pump Type	Metering Pump	Metering Pump	Metering Pump	Metering Pump	Metering Pump
Clean-out intervals	1000 hours	1000 hours	1000 hours	1000 hours	800 hours
Air Compressor	Optional	Optional	Optional	Optional	Optional
Air Requirements	25 psi / 2cfm	25 psi / 2cfm	25 psi / 2cfm	25 psi / 2cfm	25 psi / 2cfm
Safety Listings	UL / ULc	UL / ULc	UL / ULc	UL / ULc	UL / ULc, ASME
Hanging Dimension	77"L x 28"H x 27"W	83"L x 28"H x 27"W	100"L x 28"H x 27"W	111"L x 32"H x 29"W	67"L x 42"H x 34"W
Hanging weight	429#	452#	525#	625#	
shipping weight	519#	542#	615#	715#	1580#
Warranty	10 Year, 2 Year Parts	10 Year, 2 Year Parts	10 Year, 2 Year Parts	10 Year, 2 Year Parts	10 Year, 2 Year Parts 0-5 free, 6-10 50/50

Clean Energy Heating Systems
 540 Maple St
 Honey Brook, PA 19344

888.519.2347