

DEALER HOT WATER PRESSURE WASHERS

Portable Electric

Direct Drive | DHS Series



This electric pressure washer is built for industrial cleaning where proper ventilation may not be accessible. It features a top-fired heat exchanger that is completely accessible.



DH-2003-SEOE2G

Pump

- Direct drive triplex piston General or Mi-T-M pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- High pressure detergent injector
(Available as an option on SEOE1M and SEOE2M models)

Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord

Components

- Energy-efficient top-fired heat exchanger designed for convenient troubleshooting and easy maintenance
- No. 1 or No. 2 diesel or kerosene fired burner
(Not approved for bio-fuel)

Frame

- Reinforced powder coated steel tube frame with center balanced lift
- 13-inch flat-free tires

Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

Mi-T-M Pressure Relief Start:

- Equipped with the Mi-T-M Pressure Relief Start (SEOE1M and SEOE2M models) which eliminates pressure build up in the system. No need to trigger the gun when starting the pressure washer.



DEALER HOT WATER PRESSURE WASHERS

Portable Electric

Direct Drive | DHS Series



Model Number	PSI	GPM	Horsepower/Motor	Pump	Plug Type	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DH-1002-SE0E1G	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	418 lb.	295 lb.
DH-1002-SE0E1M	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	Mi-T-M	NEMA 5-15P	4.0 gallons	1.33 gph	186,000	43x29.5x36.5in.	410 lb.	237 lb.
DH-1502-SE0E1G	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	General	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	422 lb.	299 lb.
DH-1502-SE0E1M	1500	2.0	2.0 HP, 120V, 1Ø, 19.0A	Mi-T-M	NEMA 5-20P	4.0 gallons	1.21 gph	169,000	43x29.5x36.5in.	414 lb.	291 lb.
DH-2003-SE0E2G	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	General	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	439 lb.	316 lb.
DH-2003-SE0E2M	2000	2.8	4.0 HP, 230V, 1Ø, 18.0A	Mi-T-M	NEMA 6-20P	4.0 gallons	1.48 gph	207,200	43x29.5x36.5in.	431 lb.	308 lb.

Options:		
Part Number	Description	Fits Models
HX-0232	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1G
HX-0233	Adjustable thermostat - Operator is able to adjust outlet water temperature between 86°-248°F	All models
HX-0235	Hour meter - Displays number of hours unit has been in operation	All models
HX-0237	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	DH-1002-SE0E1M
HX-0238	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	DH-1002-SE0E1M
HX-0239	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1002-SE0E1M
HX-0240	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2003-SE0E2G
HX-0241	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-2003-SE0E2M
HX-0243	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	2000-PSI models
HX-0244	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	2000-PSI models
HX-0245	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1502-SE0E1M
HX-0246	300°F steam - Reduces pressure to 350-PSI by adjusting unloader valve counter-clockwise, spray temperatures will rise 240°F above ambient with a maximum of 300°F	DH-1502-SE0E1G
HX-0275	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	DH-1502-SE0E1M
HX-0276	Time delay shutdown - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	DH-1502-SE0E1M

Accessories:		
Part Number	Description	Fits Models
50-0161	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models
850-0433	50-ft. x 3/8-inch high pressure hose - For when you need extra hose for added mobility	All models



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug



NEMA 6-20P,
20-amp plug

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.